ADA185943

MEMORANDUM REPORT BRL-MR-3608

DESIGN OF A SYSTEM FOR CUTTING SHAPED CHARGE JETS FOR PENETRATION EXPERIMENTS

ROBERT E. FRANZ WILLIAM LAWRENCE

JUNE 1987

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

US ARMY BALLISTIC RESEARCH LABORATORY ABERDEEN PROVING GROUND, MARYLAND

Destroy this report when it is no longer needed. Do not return it to the originator.

Additional copies of this report may be obtained from the National Technical Information Service, U. S. Department of Commerce, Springfield, Virginia 22161.

The findings in this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.

The use of trade names or manufacturers' names in this report does not constitute indorsement of any commercial product.

SECURITY CLASSIFICATION OF THIS PAGE

REPORT DOCUMENTATION PAGE				,	Form Approved OM8 No 0704-0188 Exp. Date: Jun 30, 1986
1a REPORT SECURITY CLASSIFICATION Unclassified	1b. RESTRICTIVE MARKINGS				
2a SECURITY CLASSIFICATION AUTHORITY		3. DISTRIBUTION/AVAILABILITY OF REPORT Approved for public release; distribution			
2b. DECLASSIFICATION/DOWNGRADING SCHEDU	LE	is unlimited.			, alstribation
4. PERFORMING ORGANIZATION REPORT NUMBE	R(S)	5. MONITORING	ORGANIZATION REP	PORT NU	UMBER(S)
6a NAME OF PERFORMING ORGANIZATION Ballistic Research Laboratory	6b. OFFICE SYMBOL (If applicable) SLCBR-TB-S	7a. NAME OF MO	ONITORING ORGAN	IZATION	
6c. ADDRESS (City, State, and ZIP Code)	L	7b. ADDRESS (Cit	ty, State, and ZIP Co	ode)	
Aberdeen Proving Ground, MD 2	1005-5066				
8a. NAME OF FUNDING / SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMEN	T INSTRUMENT IDEI	NTIFICAT	TION NUMBER
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF I	FUNDING NUMBERS		
oc. Applicas (city, state, and 211 code)		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.	WORK UNIT ACCESSION NO
			11.161102-AH	3	
11. TITLE (Include Security Classification)					
Design of a System for Cutting	Shaped Charge Je	ets for Pene	tration Exper	riment	S
12 PERSONAL AUTHOR(S) Franz, Robert E. and Lawrence,	William				
13a. TYPE OF REPORT 13b. TIME CO	OVERED	14. DATE OF REPO	DRT (Year, Month, D	lay) 15	5. PAGE COUNT
16. SUPPLEMENTARY NOTATION		-u, -cu			
17. COSATI CODES FIELD GROUP SUB-GROUP	18. SUBJECT TERMS (Shaped-Charge			identify	by block number)
19 04	Shaped-Charge	e det, det r	eneciación		
10 ARSTRACT (Continue on reverse if necessary	and identify by block r	number)			
An experimental system to selectively cut a copper jet from a 34.9 mm diameter shaped-charge is described. Parameters for the uncut jet are also given. The system was designed to be used in the study of jet penetration in glass and ceramic targets.					
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT		21. ABSTRACT SI	ECURITY CLASSIFICA	TION	
XX UNCLASSIFIED/UNLIMITED	RPT. 🔲 DTIC USERS	Unclassi	fied		
22a NAME OF RESPONSIBLE INDIVIDUAL Robert Franz		226 TELEPHONE (301) 278	(Include Area Code) -6048	22c C	DEFICE SYMBOL LCBR-TB-S

TABLE OF CONTENTS

		<u>Pa</u>	ge
		LIST OF ILLUSTRATIONS	v
Paragraph	1.	INTRODUCTION	1
•	2.	EXPERIMENTAL PROCEDURE	1
	3.	EXPERIMENTS WITH THE CONE-LINER SHAPED CHARGE	2
	4.	DESIGNING A CUTTING CHARGE	2
	5.	EXPERIMENTAL SYSTEM FOR CUTTING JETS	6
	6.	CONCLUSIONS	4
		DISTRIBUTION LIST	5

LIST OF ILLUSTRATIONS

			Page
FIGURE	1.	Conical-Liner Shaped Charge	9
	2.	Velocity vs. Distance for Jet Particles, from Test 14	10
	3.	Linear Charge with Triangular Liner	11
	4.	Linear Charge with Line Wave Generator	13
	5•	Linear Charge with Semi-Circular Liner	14
	6.	Jet Cutting System	16
	7.	X-ray of Cut Jet	17
	8.	X-ray of Cut Jet	18
	9.	X-ray of Cut Jet after Penetrating Mild Steel Plate	18

1. INTRODUCTION

A shaped charge is a jet forming device consisting of an explosive charge containing a cavity. The cavity is lined with a thin metallic layer called a liner. Circular cylindrical charges with either conical or hemispherical lined cavities are extensively used as penetrators in many antiarmor applications. There are also charges with linear cavities having triangular or semicircular cross section, so called "cutting charges". These charges, as the name implies, are used to cut plates or similar configurations usually made of metal.

When a regular cone-liner shaped charge is detonated, the high pressure detonation products collapse the metal liner upon itself and form a high velocity, cylindrical, metallic jet. The jet produced can penetrate high strength materials. During the collapse process different parts of the jet experience different collapse velocities producing a velocity gradient in the jet. The tip of the jet travels faster than each succeeding portion. This gradient causes the jet to stretch and eventually fracture into a series of discrete particles. In the case of the cutting charge, the jet formed has lateral extent, which produces a slit or cut in the target instead of the circular hole produced by a conical liner.

The subject of this report is experiments in which a 150 KV flash X-ray system was used to determine the parameters of the jet formed by a regular conical liner shaped charge and to design a cutting charge. The cutting charge was used to selectively cut the jet produced by the conical shaped charge so that different velocities or lengths could be directed to the targets. This experimental system was designed to be used in the study of jet penetration in glass and ceramic target materials.

2. EXPERIMENTAL PROCEDURE

A two channel 150 KV flash X-ray system* was used to observe the jet following the standard shadowgraph technique in which the jet interupts a short duration X-ray beam and produces a shadow of itself on film mounted behind. Two exposures at different times on the same film allow the determination of the velocity and position of each jet particle. The position of the film with respect to the base of the charge and the magnification of the image caused by the beam divergence were determined by fiducial marks exposed on the film prior to the experiment. This was done by placing a lead sheet, 3.12 mm thick with a pattern of 3.3 mm diameter drilled holes, in the proposed jet path. The X-ray tubes were then fired with the film in place. This produced a double pattern of circular images on the film with known separation distances in the plane of the jet. The lead sheet was subsequently removed when the experiments were performed.

¹Birkhoff, G., MacDougal, D. P., Pugh, E. M., and Taylor, G. I., "Explosives with Lined Cavities," <u>Journal of Applied Physics</u>, Vol 19, No. 6, p. 563, June 1948.

^{*}Hewlett-Packard, McMinville, OR

The X-ray film and suitable intensifier screens* were placed in a felt-lined steel cassette with a 12.7 mm thick polyethylene cover plate on the side exposed to the X-ray beams. This protected the film from the explosive blast and the disturbances caused by the propagating jet. The times between X-ray pulses were measured with both the trigger signals and the signals from the X-ray tube current monitors and were displayed on digital oscilloscopes**. The detonators were fired using a high voltage (4KV) pulse power supply which permitted sub-microsecond timing of the explosive event.

3. EXPERIMENTS WITH THE CONE-LINER SHAPED CHARGE

The unconfined shaped charge used in this study is shown in Figure 1. The copper liner is 0.91 mm thick and has a rounded apex. The figure gives other essential dimensions of the charge and the parts of the explosive train. Various jet parameters were measured in 6 experiments examining three complete jets and three jets truncated with the cutting charge.

The velocities and the distance from the base of the charge were measured for all particles which appeared on both dynamic exposures of the films. A linear least squares fit was made of these velocity-distance data for each jet at the two exposure times. The intersections of these lines with the distance axis gave the virtual origin of the jet. For the 6 experiments, 12 values were obtained. The average value for the distance of the origin from the base of the liner was -45.5 ± 0.8 mm. Figure 2 shows a plot of the data from test No. 14. The average jet tip velocity was 7.84 ± 0.04 km/s. The breakup time of the jet was measured from particle lengths to be 40.1 microseconds after detonator firing or 20.7 microseconds from the time the jet tip reached the base of the charge. This corresponds to 4.64 charge diameters. The jet diameter was approximately 1.0 mm with an average particle length of 2.6 mm.

4. DESIGNING A CUTTING CHARGE


The cutting charge was designed with two purposes in mind. The first purpose was to produce a leading particle of sufficient areal extent and velocity to quickly cut a passing jet fired perpendicular to it. The second was to deflect the remaining jet and slug so that they would miss a hole in a plate of armor steel through which the first part of the jet had passed. It was supposed that a charge of sufficient size to accomplish the first purpose would also achieve the second.

Preliminary experiments were performed using triangular liners made from 1.35 mm thick copper sheet bent to form a trough with a 45° apex angle. A rectangular box made of acrylic plastic was placed around the

^{*}Kronex NDT 91 X-ray Film, 3M TriMax12 Screens

^{**}Nicolet Oscilloscope Div., Madison, WI. (Model 2000, 204A Plug-in)

²Chou, P. C., and Carleone, J., "Shaped Charge Jet Break Up Studies Using Radiographic Measurement and Surface Instability Calculations," ARBRL CR-337, 1977.



0.91 mm Thick Copper liner

Figure 1. Conical-Liner Shaped Charge

Figure 2. Velocity vs Distance for Jet Particles, from Test 14




Figure 3. Linear Charge With Triangular Liner

liner and filled with C-4 plastic explosive. Figure 3 gives dimensions and details of the charge and the explosive train. This charge did not produce a leading particle of sufficient size. One experiment was performed in which the liner length was increased from 39 mm to 75 mm. The explosive was detonated along a center line above the liner apex with a Deta-sheet* line wave generator instead of at the center of the charge (see Figure 4). This design did not form a good leading particle either, although the velocity of the particle that did form was higher (5.73 km/s).

A new charge was then designed using a liner with a semi-circular cross section. The liner was made by cutting regular commercial copper tubing into two halves. The tubing had a wall thickness of 1.57 mm, an outside diameter of 34.9 mm, and a length of 50.8 mm. The charge was a cube of C-4 plastic explosive 50.8 mm on a side with a cavity for the liner in the middle of one face. An acrylic plastic box surrounded the explosive and liner. The charge was detonated along the cylindrical axis of the liner in the same manner as the charge of Figure 4. Figure 5 shows the charge and gives dimensions.

This design yielded a usable leading particle which traveled at a comparably reduced yet acceptable velocity of 3.03 km/s. Experiments were then performed to cut the regular conical liner jets. These experiments are described in Section 5. In order to make construction of the cutting charges easier, reusable aluminum molds were made and Composition B explosive replaced C-4 in a charge of the same dimensions. This change gave a slightly higher leading particle velocity of 3.16 km/s. Table I gives details of the four different cutting charge designs.

5. EXPERIMENTAL SYSTEM FOR CUTTING JETS

The experimental system that was finally used is shown in Figure 6. The conical shaped charge is supported by a piece of aluminum alloy tubing with a 12.7 mm wide slot cut into its side so as not to disturb the cutting jet. The initial portion of the penetrating jet passes through a 9.5 mm diameter hole in a 25.4 mm thick plate of armor steel. The rest of the jet and the slug are deflected by the cutting charge, miss the hole, and are stopped by the steel plate. Different lengths of jet can be cut by changing the position of the cutting charge with respect to the aluminum tube support or by changing the timing of the detonation of the charges. The spacing and timing must be controlled so that the cutting charge does not interfere with the formation of the penetrating jet. Figure 7 is an X-ray of a jet cut when it was approximately 98 mm long, just before breakup.

In order to select different velocities or sections of the jet, the jet was made to penetrate mild steel plates and wipe off its leading part. Figures 8 and 9 show X-rays of a jet cut off at the same length but in the case of Figure 9 also penetrating a 6.36 mm mild steel plate placed at a 60° angle to the jet path. As can be seen, the first particles of the jet are wiped off and the tail is cleaned up. Table II gives velocities of the individual jet particles in the two X-rays.

^{*}E. I. Dupont de Nemours and Co., Inc., Explosives Product Division, Wilmington, DE 19898.




Figure 4. Linear Charge With Line Wave Generator




Figure 5. Linear Charge With Semi-Circular Liner

TABLE I

DESIGN		COPPER	LINER			LEADING
NO.	WIDTH OR DIAMETER	LENGTH	THICKNESS	SHAPE	EXPLOSIVE	PARTICLE
	mm	· mm	mm			VELOCITY km/s
1	37	39	1.37	٧	C-4	5. 34
2	38	75	1.37	٧	C-4	5. 73
3	34.9	50.8	1.57	SEMI- CIRCULAR	C-4	3. 03
4	34.9	50.8	1.57	SEMI- CIRCULAR	СОМРВ	3. 16




Figure 6. Jet Cutting System




Figure 7. X-ray of Cut Jet




Figure 8. X-ray of Cut Jet




Figure 9. X-ray of Cut Jet after Penetrating
Mild Steel Plate

TABLE II

PARTICLE NO.	JET PARTICLE VELOCITY KM/S					
	TEST	NO.				
	20	21				
1	-	7.77				
2	_	7.67				
3	_	7.62				
4	-	7.48				
5	-	7.33				
6	-	7.19				
7	7.05	7.09				
8	6.95	6.95				
9	6.87	6.80				
10	6.68	6.65				
11	6.59	6.41				

6. CONCLUSIONS

A system has been designed to selectively cut a shaped-charge jet from a comparatively small conical liner. This will allow the study of the effect of jet velocity and length in penetration of different materials. This system was designed to be used in studying penetration in glass and ceramic targets in a small indoor blast chamber where these highly fragmenting targets are contained in steel and recovered. A similar system could be designed for larger charges and targets of different materials.

	DISTRI	BUTION LIST	
No. o	f	No. of	
Copie	s <u>Organization</u>	<u>Copies</u> <u>Organization</u>	
12	Administrator Defense Technical Info Center ATTN: DTIC-FDAC Cameron Station, Bldg 5 Alexandria, VA 22304-6145	1 Commander US Army Armament, Munitio and Chemical Command ATTN: AMSMC-IMP-L Rock Island, IL 61299-73	
1	Deputy Assistant Secretary of the Army (R&D) Department of the Army Washington, DC 20310	1 Commander U.S. Army ARDEC ATTN: SMCAR-TDC Dover, NJ 07801-5001	
1	HQDA DAMA-ARP-P, Dr. Watson Washington, DC 20310	<pre>1 Commander U.S. Army ARDEC ATTN: SMCAR-TSS Dover, NJ 07801-5001</pre>	
1	HQDA DAMA-ART-M Washington, DC 20310	1 Director U.S. AMCCOM ARDEC CCAC	
1	HQDA DAMA-MS Washington, DC 20310	Benet Weapons Laboratory ATTN: SMCAR-CCB-TL Watervliet, NY 12189-405	0
	C.I.A. OIR/DB/Standard GE47 HQ Washington, DC 20505 Commander	1 Commander US Army Aviation Systems Command ATTN: AMSAV-ES 4300 Goodfellow Boulevard St. Louis, MO 63120-1798	
·	US Army War College ATTN: Lib Carlisle Barracks, PA 17013	1 Director US Army Aviation Research and Technology Activity Ames Research Center	
1	Commander US Army Command and General Staff College ATTN: Archives Fort Leavenworth, KS 66027	Moffett Field, CA 94035- 1 Commander US Army Communications - Electronics Command ATTN: AMSEL-ED	1099
1	Commander US Army Materiel Command ATTN: AMCDRA-ST	Fort Monmouth, NJ 07703-	5301

5001 Eisenhower Avenue Alexandria, VA 22333-0001 CECOM R&D Technical Library

Section), B.2700 Fort Monmouth, NJ 07703-5000

ATTN: AMSEL-IM-L (Reports

No. of Copies Organization Copies Organization

- 1 Commander
 US Army Development and
 Employment Agency
 ATTN: MODE-ORO
 Fort Lewis, WA 98433-5000
- 1 Commander
 US Army Harry Diamond
 Laboratory
 ATTN: SLCHD-DE-OS
 2800 Powder Mill Road
 Adelphi, MD 20783
- 1 Commander
 MICOM Research, Development
 and Engineering Center
 ATTN: AMSMI-RD
 Redstone Arsenal, AL
 35898-5500
- 1 Director
 Missile and Space
 Intelligence Center
 ATTN: AIAM-S-YDL
 Redstone Arsenal, AL
 35898-5500
- 1 Commander
 US Army Ballistic Missile
 Defense Systems Command
 ATTN: SENSC, Mr. Davidson
 P. O. Box 1500
 Huntsville, AL 35804
- 3 Director
 BMD Advanced Technology Center
 ATTN: ATC-T, M. Capps
 ATC-M, S. Brockway
 ATC-RN, P. Boyd
 P.O. Box 1500, West Station
 Huntsville, AL 35807

Commander
US Army Mobility Equipment
Research & Development
Command
ATTN: DRDME-WC
DRDME-RZT
Fort Belvoir. VA 22060

- 1 Commander US Army Natick Research and Development Center ATTN: DRXRE, Dr. D. Sieling Natick, MA 01762
- 1 Commander
 US Army Tank Automotive
 Command
 ATTN: AMSTA-TSL
 Warren, MI 48397-5000
 - 1 Commander
 USAG
 ATTN: Tech Lib
 Fort Huachuca, AZ 85613-6000
- US Army Laboratory Command
 Materials Technology
 Laboratory
 ATTN: AMXMR-T, J. Mescall
 AMXMR-T, R. Shea
 AMXMR-H, S. C. Chou
 Watertown, MA 02172-0001

3 Commander

- 1 Commander
 US Army Research Office
 P. O. Box 12211
 Research Triangle Park,
 NC 27709
- 1 Director
 US Army TRADOC Analysis Center
 ATTN: ATOR-TSL
 White Sands Missile Range,
 NM 88002-5502

No. o: Copie:		No. of Copies	
1	Commandant US Army Infantry School ATTN: ATSH-CD-CS-OR Fort Benning, GA 31905-5400	5	Commander US Naval Research Laboratory ATTN: C. Sanday R. J. Weimer Code 5270, F. MacDonald
2	Office of Naval Research Department of the Navy ATTN: Code 402 Washington, DC 20360		Code 2020, Tech lib Code 7786, J. Baker Washington, DC 20375
1	Commander US Naval Air Systems Command ATTN: AIR-604 Washington, DC 20360	7	Commander Naval Research Laboratory Engineering Materials Division ATTN: E. A. Lange G. R. Yoder C. A. Griffis
1	Commander Naval Sea Systems Command ATTN: Code SEA 62D Department of the Navy Washington, DC 20362-5101		R. J. Goode R. W. Judy, Jr. A. M. Sullivan T. W. Crooker Washington, DC 20375
4	Commander Naval Surface Weapons Center ATTN: Code Gr-9, Dr. W. Soper Dr. W. H. Holt Dr. W. Mock Tech Lib Dahlgren, VA 22448-5000	1	AFWL/SUL Kirtland AFB, NM 87117 RADC (EMTLD, Lib) Griffiss AFB, NY 36112 AUL (3T-AUL-60-118) Maxwell AFB, AL 36112
3	Commander Naval Surface Weapons Center ATTN: Dr. R. Crowe Code R32, Dr. S. Fishman Tech Lib Silver Spring, MD 20902-5000	5	Air Force Armament Laboratory ATTN: AFATL/DOIL (Tech Info Center) J. Foster John Collins Joe Smith Guy Spitale
1	Commander and Director US Naval Electronics Laboratory ATTN: Lib San Diego, CA 92152	2	Eglin AFB, FL 32542-5438 Air Force Wright Aeronautical Laboratories Air Force Systems Command Materials Laboratory ATTN: Dr. Theodore Nicholas Wright-Patterson AFB, OH 45433

No. of		No. of Copies	
1	Air Force Wright Aeronautical Laboratories Air Force Systems Command Materials Laboratory ATTN: Dr. John P. Henderson Wright-Patterson AFB, OH 45433		Honeywell, Inc. Defense Systems Division ATTN: Dr. Gordon Johnson 600 Second Street, NE Hopkins, MN 55343 Orlando Technology, Inc.
1	Director Environmental Science Service Administration US Department of Commerce Boulder, CO 80302	7	ATTN: Dr. Daniel Matuska Dr. John J. Osborn P. O. Box 855 Shalimar, FL 32579 SRI International
1	Director Lawrence Livermore Laboratory ATTN: Dr. M. L. Wilkins P. O. Box 808 Livermore, CA 94550		ATTN: Dr. G. R. Abrahamson Dr. D. Curran Dr. L. Seaman Dr. D. A. Shockey Mr. D. Erlich Dr. A. Florence Dr. R. Caligiuri
6	Sandia National Laboratories ATTN: Dr. L. Davison Dr. P. Chen Dr. L. Bertholf Dr. W. Hermann Dr. J. Nunziato Dr. S. Passman P. O. Box 5800 Albuquerque, NM 87185	1	333 Ravenswood Avenue Menlo Park, CA 94025 Systems Planning Corporation ATTN: Mr. T. Hafer 1500 Wilson Boulevard Arlington, VA 22209
1	Director Jet Propulsion Laboratory ATTN: Lib (TDS) 4800 Oak Grove Drive Pasadena, CA 91103		ATTN: Dr. Arfon Jones 420 Wahara Way University Research Park Salt Lake City, UT 84108 California Institute of
1	Director National Aeronautics and Space Administration Lyndon B. Johnson Space Center ATTN: Lib Houston, TX 77058		Technology Division of Engineering and Applied Science ATTN: Dr. J. Mikowitz Dr. E. Sternberg Dr. J. Knowles Pasadena, CA 91102
1	A.R.A.P. Group, Titan Systems, Inc. ATTN: Dr. Coleman Donaldson 1800 Old Meadow Rd., #114 McLean, VA 22102	1	Denver Research Institute University of Denver ATTN: Dr. R. Recht P. O. Box 10127 Denver, CO 80210

No. of Copies		No. of Copies	
	Rensselaer Polytechnic Institute ATTN: Prof. E. H. Lee Prof. E. Krempl Prof. J. Flaherty Troy, NY 12181		Cornell University Department of Theoretical and Applied Mechanics ATTN: Dr. Y. H. Pao Dr. G. S. S. Ludford Dr. A. Ruoff Dr. J. Jenkins
	Southwest Research Institute ATTN: Dr. Charles Anderson 6220 Culebra Road P. O. Drawer 28510		Dr. R. Lance Dr. F. Moon Ithaca, NY 14850
	San Antonio, TX 78284 Southwest Research Institute Department of Mechanical	2	Forrestal Research Center Aeronautical Engineering Lab. Princeton University ATTN: Dr. S. Lam
	Sciences ATTN: Dr. U. Kindholm 8500 Culebra Road San Antonio, TX 78228	1	Dr. A. Eringen Princeton, NJ 08540 Harvard University
1	University of Dayton Research Institute ATTN: Dr. S. J. Bless Dayton, OH 45469		Division of Engineering and Applied Physics ATTN: Prof. J. R. Rice Cambridge, MA 02138
		2	Iowa State University
	Brown University Division of Engineering ATTN: Prof. R. Clifton Prof. H. Kolsky Prof. L. B. Freund Prof. A. Needleman		Engineering Research Laboratory ATTN: Dr. G. Nariboli Dr. A. Sedov Ames, IA 50010
	Prof. R. Asaro Prof. R. James Providence, RI 02912	2	Lehigh University Center for the Application of Mathematics ATTN: Dr. E. Varley
	Catholic University of America School of Engineering and Architecture		Dr. R. Rivlin Bethlehem, PA 18015
	ATTN: Prof. A. Durelli Prof. J. McCoy Washington, DC 20017	1	New York University Department of Mathematics ATTN: Dr. J. Keller University Heights New York, NY 10053

No. of Copies	Organization	No. of Copies	
1	North Carolina State University Department of Civil Engineering ATTN: Prof. Y. Horie Raleigh, NC 27607		University of California ATTN: Dr. M. Carroll Dr. W. Goldsmith Dr. P. Naghdi Berkeley, CA 94704
] 1	Pennsylvania State University Engineering Mechanical Department ATTN: Prof. N. Davids University Park, PA 16502	1	University of California Department of Aerospace and Mechanical Engineering Science ATTN: Dr. Y. C. Fung P. O. Box 109 La Jolla, CA 92037
1	Rice University ATTN: Dr. R. Bowen Dr. C. C. Wang P. O. Box 1892 Houston, TX 77001 Southern Methodist University	1	University of California Department of Mechanics ATTN: Dr. R. Stern 504 Hilgard Avenue Los Angeles, CA 90024
1	Solid Mechanics Division ATTN: Prof. H. Watson Dallas, TX 75221 Temple University College of Engineering	1	University of California at Santa Barbara Department of Mechanical Engineering ATTN: Prof. T. P. Mitchel Santa Barbara, CA 93106
ц.	Technology ATTN: Dr. R. Haythornthwaite, Dean Philadelphia, PA 19122 The Johns Hopkins University	1	University of Delaware Department of Mechanical Engineering ATTN: Prof. J. Vinson Newark, DE 19711
	ATTN: Prof. R. B. Pond, Sr. Prof. R. Green Prof. W. Sharpe Prof. J. Bell 34th and Charles Streets Baltimore, MD 21218	3	University of Florida Department of Engineering Science and Mechanics ATTN: Dr. C. A. Sciammarilla Dr. L. Malvern Dr. E. Walsh
	Tulane University Department of Mechanical Engineering ATTN: Dr. S. Cowin New Orleans, LA 70112	2	Gainesville, FL 23601 University of Houston Department of Mechanical Engineering ATTN: Dr. T. Wheeler Dr. R. Nachlinger Houston, TX 77004

	DISIKI	ROLION	LIST
No. of Copies		No. of Copies	
	University of Illinois Department of Theoretical and Applied Mechanics ATTN: Dr. D. Carlson Urbana, IL 61801 University of Illinois		University of Texas Department of Engineering Mechanics ATTN: Dr. M. Stern Dr. M. Bedford Prof. Ripperger Dr. J. T. Oden
	ATTN: Dean D. Drucker Urbana, IL 61801		Austin, TX 78712 University of Washington
1	University of Illinois at Chicago Circle College of Engineering Department of Materials Engineering ATTN: Dr. T. C. T. Ting P. O. Box 4348		Department of Aeronautics and Astronautics ATTN: Dr. Ian M. Fyfe 206 Guggenheim Hall Seattle, WA 98195
	Chicago, IL 60680		Washington State University Department of Physics ATTN: Dr. R. Fowles
2	University of Kentucky Department of Engineering Mechanics ATTN: Dr. M. Beatty		Dr. G. Duvall Dr. Y. Gupta Pullman, WA 99163
	Prof. O. Dillon, Jr. Lexington, KY 40506	2	Yale University ATTN: Dr. B. T. Chu Dr. E. Onat
1	University of Maryland Department of Mathematics ATTN: Prof. S. Antman College Park, MD 20742		400 Temple Street New Haven, CT 96520
	-		

1 University of Minnesota Department of Aerospace

Minneapolis, MN 55455

1 University of Pennsylvania

ATTN: Prof. Z. Hashin Philadelphia, PA 19105

Towne School of Civil and

Mechanical Engineering

107 Akerman Hall

Engineering and Mechanics

ATTN: Prof. J. L. Erickson

Aberdeen Proving Ground

Dir, USAMSAA
ATTN: AMXSY-D
AMXSY-MP, H. Cohen
Cdr, USATECOM
ATTN: AMSTE-SI-F
Cdr, CRDC, AMCCOM
ATTN: SMCCR-RSP-A
SMCCR-MU
SMCCR-SPS-IL

USER EVALUATION SHEET/CHANGE OF ADDRESS

This Laboratory undertakes a continuing effort to improve the quality of the reports it publishes. Your comments/answers to the items/questions below will aid us in our efforts.

1. BRL Rep	oort Number	Date of Report
2. Date Re	eport Received	
	nis report satisfy a need? (Com of interest for which the repor	ment on purpose, related project, or t will be used.)
	edure, source of ideas, etc.)	used? (Information source, design
as man-hour		to any quantitative savings as far costs avoided or efficiencies achieved
		chould be changed to improve future on, technical content, format, etc.)
	Name	
CURRENT	Organization	
ADDRESS	Address	
	City, State, Zip	
		ddress Correction, please provide the dthe Old or Incorrect address below.
	Name	
OLD ADDRESS	Organization	
	Address	
	City, State, Zip	

(Remove this sheet along the perforation, fold as indicated, staple or tape closed, and mail.)

Director U.S. Army Ballistic Research ATTN: SLCBR-DD-T Aberdeen Proving Ground, MD		E — — — — — —	NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES
OFFICIAL BUSINESS PENALTY FOR PRIVATE USE, \$300	BUSINESS REFIRST CLASS PERMIT NO POSTAGE WILL BE PAID BY DE	12062 WASHINGTON, DC	
ATTN:	or Trmy Ballistic Resear SLCBR-DD-T een Proving Ground,		

- -- FOLD HERE ---